

**STAINLESS STEEL 2PC SCREWED HOSE END BALL VALVE WITH SS 304/316 SPARES.**



- 2PC Body Design
- Full Bore
- Precision Investment Casted
- Sizes Available from 15MM To 50MM
- Blow Out Proof Stem
- Handle with Locking Device available on request
- Testing Pressure : 1000PSIG (HYD)
- Testing Standard : BS EN 17292
- Screwed Threaded Ends confirming to : BS21 BSP/BSPT/NPT/ISO228 & ISO 7/1
- Suitability : WATER, OIL, GAS, STEAM, AIR

SIZE
8MM/ 1/4"
10MM/ 3/8"
15MM/ 1/2"
20MM/ 3/4"
25MM/1"
32MM/ 1-1/4"
40MM/ 1-1/2"
50MM/ 2"
65MM/ 2-1/2"
80MM/3"
100MM/ 4"

**STAINLESS STEEL 2PC SCREWED MALE END BALL VALVE WITH SS 304/316 SPARES.**



- 2PC Body Design
- Full Bore
- Precision Investment Casted
- Sizes Available from 15MM To 50MM
- Blow Out Proof Stem
- Handle with Locking Device available on request
- Testing Pressure : 1000PSIG (HYD)
- Testing Standard : BS EN 17292
- Screwed Threaded Ends confirming to : BS21 BSP/BSPT/NPT/ISO228 & ISO 7/1
- Suitability : WATER, OIL, GAS, STEAM, AIR

SIZE
8MM/ 1/4"
10MM/ 3/8"
15MM/ 1/2"
20MM/ 3/4"
25MM/1"
32MM/ 1-1/4"
40MM/ 1-1/2"
50MM/ 2"
65MM/ 2-1/2"
80MM/3"
100MM/ 4"

**STAINLESS STEEL 2PC SCREWED END BALL VALVE WITH SS 304/316 SPARES.**



- 2PC Body Design
- Full Bore
- Precision Investment Casted
- Sizes Available from 8MM To 100MM
- Blow Out Proof Stem
- Handle with Locking Device available on request
- Testing Pressure : 1000PSIG (HYD)
- Testing Standard : BS EN 17292
- Screwed Threaded Ends confirming to : BS21 BSP/BSPT/NPT/ISO228 & ISO 7/1
- Suitability : WATER,OIL,GAS,STEAM,AIR

SIZE
8MM/ 1/4"
10MM/ 3/8"
15MM/ 1/2"
20MM/ 3/4"
25MM/1"
32MM/ 1-1/4"
40MM/ 1-1/2"
50MM/ 2"
65MM/ 2-1/2"
80MM/3"
100MM/ 4"

**STAINLESS STEEL 3PC SCREWED/SOCKET/BUTT WELD  
END BALL VALVE WITH SS 304/316  
SPARES, AS PER CLASS 150**



- Full Port & 3 Pc Body Construction
- Size Range 15MM To 50MM (DN 15 to DN 50)
- Design Standard BSEN ISO 17292 (BS 5351)
- Blow Out Proof Stem
- Handle with Locking Device available on request
- Class - 150
- Hydraulic Body Test 62 Kg/CM<sup>2</sup>
- Hydraulic Seat Test 45 Kg/CM<sup>2</sup>
- Pneumatic Seat Test 4-7 Kg/CM<sup>2</sup>
- Precision Investment Casted
- Screwed Threads To –  
BS 21 BSP/BSPT/NPT/DIN 259/2999 & ISO 228 & ISO 7/1
- Screwed Female Ends/Socket Weld Ends/Butt Weld Ends
- Suitability : WATER, OIL, GAS, AIR
- Also available for STEAM application upon request

SIZE
8MM/ 1/4"
10MM/ 3/8"
15MM/ 1/2"
20MM/ 3/4"
25MM/1"
32MM/ 1-1/4"
40MM/ 1-1/2"
50MM/ 2"
65MM/ 2-1/2"
80MM/3"
100MM/ 4"

**STAINLESS STEEL 3PC FLANGED BALL VALVE  
WITH SS 304/316 SPARES, AS PER CLASS 150**



- Full Port & 3 Pc Body Construction
- Size Range 15MM To 100MM (DN 15 to DN 100)
- Design Standard BSEN ISO 17292 (BS 5351)
- Blow Out Proof Stem
- Handle with Locking Device available on request
- Flanged End conforming to Class - 150
- Hydraulic Body Test 29 Kg/CM<sup>2</sup>
- Hydraulic Seat Test 21 Kg/CM<sup>2</sup>
- Pneumatic Seat Test 4-7 Kg/CM<sup>2</sup>
- Precision Investment Casted
- Suitability : WATER, OIL, GAS, AIR
- Also available for STEAM application upon request

SIZE
8MM/ 1/4"
10MM/ 3/8"
15MM/ 1/2"
20MM/ 3/4"
25MM/1"
32MM/ 1-1/4"
40MM/ 1-1/2"
50MM/ 2"
65MM/ 2-1/2"
80MM/3"
100MM/ 4"

**STAINLESS STEEL Y-STRAINER  
SCREWED END ( DOUBLE MESH )**



- Y-Type Body
- ½" TO 2" ( DN15 TO DN 50)
- Full Bore
- Working Pressure :- 800 WOG
- Working Temperature :- (-)10° To (+)100° Celcius
- Precision Investment Casted
- Screwed Threads To – BS 21 BSP/BSPT/  
NPT/DIN 259/2999 & ISO 228 & ISO 7/1
- Suitability: WATER, OIL

SIZE
8MM/ 1/4"
10MM/ 3/8"
15MM/ 1/2"
20MM/ 3/4"
25MM/1"
32MM/ 1-1/4"
40MM/ 1-1/2"
50MM/ 2"
65MM/ 2-1/2"
80MM/3"



**STAINLESS STEEL DISC CHECK VALVE (PN40)**

- ½" TO 4" ( DN15 TO DN 100)
- Metal To Metal Seat, Soft seat available on request
- Suitable for Class 150/300 IBR & Non IBR Flanges
- Horizontal or Vertical Mounted
- Hydraulic Test Pressure :- 60 Bar
- Hydraulic Seat Test Pressure :- 44 Bar
- Working Temperature :- 425° Celcius Max
- Precision Investment Casted
- Suitability :-WATER, STEAM, OIL,

SIZE
15MM/ 1/2"
20MM/ 3/4"
25MM/1"
32MM/ 1-1/4"
40MM/ 1-1/2"
50MM/ 2"
65MM/ 2-1/2"
80MM/3"
100MM/ 4"



**STAINLESS STEEL VERTICAL CHECK VALVE (NRV) SCREWED END**

- ½" TO 2" ( DN15 TO DN 50)
- Full Bore
- Metal to Metal seat. Soft seat available on request
- Working Pressure :- 800 WOG
- Working Temperature :- (-)10° To (+)100° Celcius
- Precision Investment Casted
- Screwed Threads To – BS 21 BSP/BSPT/NPT/ DIN 259/2999 & ISO 228 & ISO 7/1
- Suitability :-WATER, OIL  
Soft Seated also available for AIR application.

SIZE
8MM/ 1/4"
10MM/ 3/8"
15MM/ 1/2"
20MM/ 3/4"
25MM/1"
32MM/ 1-1/4"
40MM/ 1-1/2"
50MM/ 2"
65MM/ 2-1/2"



**STAINLESS STEEL HORIZONTAL CHECK VALVE ( SWING TYPE NRV) SCREWED END**

- ½" TO 2" ( DN15 TO DN 50) • Full Bore
- Metal to Metal Seat, Soft seat available on request
- Working Pressure :- 200 WOG
- Working Temperature :- (-)10° To 100° Celcius
- Precision Investment Casted
- Screwed Threads To – BS 21 BSP/BSPT/NPT/ DIN 259/2999 & ISO 228 & ISO 7/1
- Screwed Female Ends/Socket Weld Optional
- Suitability :-WATER, OIL  
Also available for STEAM application upon request

SIZE
8MM/ 1/4"
10MM/ 3/8"
15MM/ 1/2"
20MM/ 3/4"
25MM/1"
32MM/ 1-1/4"
40MM/ 1-1/2"
50MM/ 2"
65MM/ 2-1/2"